

Costs of CO₂ pipeline transport for Dynamis case studies

European Conference on CCS Research,
Development and Demonstration

February 2009

Ecofys Netherlands

Erika de Visser

Chris Hendriks

Contents

I. Scope of the work

II. Pipeline costing

- Experience with CO₂ pipelines
- Economics of pipelines
- Focus on material cost


III. DYNAMIS recommended plant sites

- Route selection
- Cost calculation

Scope of the work

SP3 work focuses on infrastructure for CO₂

- DYNAMIS CO₂ quality recommendation
- Routing and costing of CO₂ pipelines



CO₂ quality recommendations

Compound	Concentration limit	Remarks
H ₂ S	200 ppm	Health and safety considerations
CO	2000 ppm	Health and safety considerations
SO _x	100 ppm	Health and safety considerations
NO _x	100 ppm	Health and safety considerations
H ₂ O	500 ppm	Technical limit
O ₂	Aquifer <4 vol% (all non cond. gases), EOR >100 ppm	Technical limit; storage issue
CH ₄	Aquifer < 4 vol%, EOR <2 vol% (all non cond. gases)	Like ENCAP
N ₂ , Ar, H ₂	<4 vol% (all non cond. gases)	Like ENCAP
CO ₂	> 95%	Result of other compounds in CO ₂



Experience with CO₂ pipelines

- Experience with the transportation of CO₂ in pipelines:
 - Ca. 3100 km CO₂ pipelines using naturally occurring CO₂ for EOR in USA
 - With a capacity of 44 Mt/yr
- But CCS projects differ, because:
 - The CO₂ is from anthropogenic origin, the quality of the CO₂ differs
 - Both long distance onshore and offshore pipelines
- Gas and oil pipelines estimates give good indications of CO₂ pipeline costs
 - With the remark that CO₂ pipeline costs can be higher due to higher operating pressures and thicker pipeline walls



CO₂ and transport characteristics

- CO₂ characteristics:
 - Dense phase -> to increase density and reduce cost
 - Recommended CO₂ purity -> >95% (Dynamis SP3.1)
- Pipeline transport characteristics:
 - Continuous flow
 - Cheaper at shorter distances (compared to ship)
- Possible (re)use of existing pipelines

OACAP pipeline


- Currently:
 - 44 kg/s
 - Gaseous, at 22 bars
 - No (additional) permits required
 - Risk assessment performed
- Suitable for higher pressures (after some limited modifications)



Economics of pipelines (1)

- Costs depend on the length and size of the pipe, terrain conditions and number and complexity of artworks, condition of the CO₂ and level of impurity, steel price, cost of labour...
- Cost shares for US land pipelines with diameter between 0.21m and 0.91m are:
 - Installation / labour: 45%
 - Material: 26%
 - Miscellaneous : 22%
 - Permits, Rights of way : 7%

Economics of pipelines (2)



With increasing pipeline diameter the proportion of material costs and miscellaneous cost increases, while the proportion of the other components decreases


Economics of pipelines (3)

- Historical pipeline investment costs of pipelines are given as:
 - 0.6 – 1.0 M€/m/km for onshore pipelines through ‘uncomplicated’ terrain excl. art works
 - 1.0 -2.0 M€/m/km for offshore pipelines
- Pipeline costs of existing CO₂ pipeline projects:
 - Snøhvit: 2.3 M€/m/km (subsea, arctic circumstances)
 - Weyburn: 0.5 M€/m/km (long distance, desert area)
- In the last years pressure on the market showed substantial increase in costs (material, labor)

Material cost (1)

- Current practice: carbon steel for transportation of 'dry CO₂'
- For (very) short transportation distances and wet CO₂ stainless steel might be economic


- Steel prices:
 - 'stable' in period '94 – '03
 - Increasing since 2003
 - Almost doubled in 4 years
 - Steel prices currently decline



Source: www.cruspi.com

Material cost (2)

- 2003 pipeline investment cost set to 100%
- Steel prices increase according to price index of steel





Base construction cost

- Estimation of CO₂ transportation cost based on base construction cost of
 - 1.7 €/m/km for land pipelines and
 - 2.7 €/m/km for sea pipelines
- Conservative estimates

Estimating CO₂ pipeline cost

Steps in calculating CO₂ transportation cost (€/tCO₂):


1. Determination of alternative pipeline trajectories, considering:
 - avoidance of urban areas
 - the possibility of following existing pipeline corridors
 - Make use of existing gas or oil terminals
2. Collection of information on trajectory specific conditions such as:
 - # of principal crossings (river, roads)
 - # of km through residential area, cultivated area etc.
 - Sea depth

Example – case study

Candidate plant site Progressive Energy Ltd.:


- Capture location: Lynemouth
- Storage location: Piper field
- 2.5 Mt CO₂/y
- diameter pipeline 0.34 m

Length (km)	Principal crossings (#)			Sea Depth (m)	Cost (€/tCO ₂)
	Main roads	Rail	Waterway		
377 km offshore	-	-	-	0 -150 m	22.6
331 km onshore 177 km offshore	32	16	182	0 -150 m	48.5
106 km onshore 440 km offshore	5	66	47	0 -150 m	42.0



(BGS, 2008)

CO₂ transportation cost



Conclusions

Main conclusions:

- Current pipeline cost are significantly higher compared to the high estimates of other studies
- Used data suggest considerable spread of costs
- Sensitivity analysis suggests that up scaling of the activities from 2.5 Mt CO₂/year leads to large cost reduction